

SC/APC Fiber Optic Fast Connector



SC/APC fiber optic fast connectors are factory terminated and polished to make fibre terminations fast, easy and reliable. These fibre optic connectors offer terminations in less than 2 minutes without any difficulty and require no epoxy, polishing or crimping. They greatly reduce the installation and set up time. It has a window feature to allow testing with a visual fault locator.

Feature

Field installation, fast connection
Easy for operation
No glue, no polishing
High performance and high reliability
Cost effective

Application

CATV
FTTH
Optical distribution frame
Optical network equipments

Specification

Items	Parameters	
Cable Diameter	Drop cable. Indoor cable(0.9/2.0/3.0mm)	
Fiber Type	G657A1, G657A2	
Operation Time	About 50s(no fiber cut)	
Insertion Loss (dB)	≤0.3 (1310nm-1550nm)	
Return Loss (dB)	PC≥45	APC≥50
Fastening strength of naked fiber(N)	>5	
Fastening strength of naked fiber holder(N)	>10	
Tensile Strength(N)	>50	
Operating Temperature (°C)	-40~+75	



USA
Fernando Chang
Tel: 1-714-990-4488
E-mail: fchang@fipos.com



China
Glenn Wu
Mobile: 86-13509658246
E-mail: sale@fipos.cn